

HC15/HC25 USB Terminal

UMTS Terminal, welches auch den HSDPA-Standard unterstützt



Features:

- **HC15:** EDGE/GPRS 900, 1800 MHz / HSDPA/UMTS 2100 MHz
- **HC25:** EDGE/GPRS 850, 900, 1800, 1900 MHz / HSDPA/UMTS 850, 1900, 2100 MHz
- EDGE (E-GPRS) multislots Klasse 10
- GPRS multislots Klasse 10
- UMTS/HSDPA/GSM 3GPP
- TCP/IP stack access via AT commands
- Eingangsspannungsbereich:
Terminal: 8 ... 30 V
Platine: 3.2 ... 4.2 V
- Betriebstemperatur: -30°C bis +65°C
- Abmessungen:
Terminal: 65 x 74 x 33 mm, Gewicht: ca. 130 g
Platine: 50 x 34 x 4.5 mm, Gewicht: ca. 10 g
- **EDGE:** Modulation and coding scheme MCS 1-9, mobile station class B
- **GPRS:** Full PBCCH support, mobile station class B, Coding scheme 1-4
- **UMTS:** max. 384 kbps (DL), max. 384 kbps (UL)
- **HSDPA:** max. 3.6 Mbps (DL), max. 384 kbps (UL), UE CAT [1-6], 11, 12 supported, Compressed mode according to 3GPP TS25.212
- **SMS:** Point-to-point MO and MT / SMS cell broadcast / Text- and PDU-mode
- **Daten:** CSD bis zu 14,4 kbps/USSD/V.110/GPRS: max. 85,6 kbps (downlink)/ Coding Scheme CS 1,2,3,4/PPP-Stack/Integrated TCP/IP stack
- **Fax:** Gruppe 3, Klasse 1
- **Features HC15 Platine:** USB 2.0 (Fullspeed), Data + Voice, NDIS for Windows™ WIN 2K, WIN XP
- **Features HC25 Platine:** USB 2.0 (Fullspeed), Data + Voice (fully featured), NDIS/RIL for Windows™ Mobile 5.0 ®
- **Schnittstellen Platine:** Hirose U.FL-R-SMT 50 Ohm Antennenstecker, Hirose 50-pin board-to-board connector: Power supply, Audio: 1 x analog, USB 2.0 full speed, UICC/SIM card interface 3 V, 1.8 V, Emergency-off
- **Schnittstellen Terminal:** RS232 Schnittstelle, USB Schnittstelle, Anschluß für Steckernetzteil, integrierter SIM-Card-Reader, FME Antennenanschluß